

Ref. 3

AN 1998-402835 (J5) WPIN
DNN N1998-313821 DNC C1998-121944
TI Conductive elastic member - produced by adding organic ion
conductive agent into thermoplastic polyurethane elastomer and
moulding.
DC A25 A60 A89 E34 G08 P84 S06 T04
PA (ARII-N) ARII GOSEI KOGYOSHO YG
CYC 1
PI JP 10161397 A 19980619 (199835)* Sp G03G015-02
ADT JP 10161397 A JP 1996-329091 19961126
PRAI JP 1996-329091 19961126
IC ICM G03G015-02
ICS C08L075-08; G03G015-16
ICI C08L071:00, C08L075-08
AB JP 10161397 A UPAB: 19980904
A conductive elastic member is prepared by adding organic ion
conductive agent into thermoplastic polyurethane elastomer and
molding it.

USE - The conductive elastic member is used for a charged
roller and a transfer belt and the like used for a copy machine, a printer
and the like.

ADVANTAGE - The conductive elastic member has less
dispersion of electric resistance value in the member and less
change by applied voltage, so that the member has excellent charge
performance and transfer performance. Since the electric resistance value
is controlled by adding amount of the organic ion conductive
agent, the conductive elastic member which has desired electric

resistance value may be provided. Since the dispersion of the
electric resistance value is less, it is not necessary to form a
resistance adjusting layer and structure of the member can be simplified
and its production cost may be reduced.
Dwg.0/0